

Akura 44 | Thumbturn cylinder Euro profile modular





Technical information

Technical information	
Cylinder lenghts	27/K27, 27/K30, 27/K35, 30/K27, 30/K30, mm Starting at 30 mm in 5 mm steps
Finish	NI – Nickel MS – Brass CP – Polished chrome CPV – Chrome fully polished CR – Chrome ML – Brass lacquered MP – Polished brass MPV – Brass fully polished NP – Polished Nickel NPV – Nickel fully polished PB – Patinated brown PS – Patinated black
Thumbturn shapes	AK – Allround thumbturn FK – Flat thumbturn GK – Recessed grip thumbturn KK – Cone thumbturn MK – Metal knurl thumbturn RK – Round thumbturn X1K – Oval thumbturn 0K – Oval thumbturn aluminium 0KA – Oval thumbturn aluminium asym. CK – D-line® thumbturn ATA – Adaptable Thumbturn Axis N0K – Without thumbturn
Thumbturn finishes	K-NI – Nickel K-MS – Brass K-CP – Polished Chrome K-CR – Chrome K-MP – Polished brass K-NP – Polished nickel K-PB – Patinated brown K-PS – Patinated black
Optional security features	AS-A – Anti-Snap outer side CLA – Classroom function MAG – Magnetic copying protection S0S – SOS function
Optional technical installation feature	BIF - Double cam Biffar® LW[] - Free travel NS-A - Increased wear resistance outside SEW - Sea water protection SW-A - Dust and weather protection outside Z[] - Cogwheel
Optional usage feature	BIF – Double cam Biffar® CLA – Classroom function LW[] – Free travel SEW – Sea water protection TXT – Customer-specific text VAR – VARIO Z[] – Cogwheel
Function	Can be locked from inside with thumbturn Can be locked with key Reversible key
Usage	connecting doors entrance doors apartment entrance metal frame door security doors
Security	Pin rows: 3 Active pins: 6 Passive pins: 10 Drilling protection Pulling protection Picking protection Security card
Standards	EN 1303:2015 160B0C6B ČSN EN 1627, Security class 4 BSI* Fire resistance 90 minutes
Assembly	Mortise lock according to DIN, ÖNORM Modular design Cam width 9,3 mm
included components	Cylinder lock Fixing screw M5
Product code	M.A44.PZ.KZ-M.[Cylinder length].[Finish].[Thumbturn shape].[Thumbturn finish].[Options]

Dimensional drawing



