


# Xesar cylinder | Half cylinder European profile SYMO HZ-S



## Product description

Xesar half cylinders are the ideal solution for doors or key switches requiring authorisation only on one side, no cylinder on the inside and maximum security requirements on the inside and outside. Additionally, Xesar half cylinders are perfectly suitable for existing doors, listed monuments as well as metal frame doors.

## Technical information

Cylinder length on the outside A in mm	31   36   41   46   + 5 mm ... Standard: A + l ≤ 92 mm, special lengths: A ≥ 97 mm
Finish	NI – nickel   NP – polished nickel   MP – polished brass   PB – brown patina   PS – black patina
Technical installation situation	FZG – free-wheel function (from 31 to 81)   FAP – anti-panic function (from 61 to 81; from 31 to 57 with install elongation module (l = 31 mm) on request   FLU – irrespective of installation position   FSR – cam latching function (31, 36, 41; from 46 to 111 on request)
Elongated outside thumbturn axis	AV05 – 5 mm   AV10 – 10 mm   AV15 – 15 mm
Cam	SEP – European profile   BIF – Biffar Z10 – Cogwheel cam 10   Z18 – Cogwheel cam 18   RIT – RITTAL cam function (31, 36)
Additional certificate	SKG – SKG***
Security features	The outside handle has been disengaged to turn freely   Rotary damper <sup>1</sup>   Rated brake point on the outside thumbturn   Engages only if authorised   Event log   Drilling protection   Plug pulling protection   AES encryption
Standards and guidelines	CE tested   EN 1634-2: 30 minutes   EN 1634-1: 90 minutes   IP65 rating   EN 15684: 1.6.B.3.A.F.3.2   Suitable for locks as per EN 179/1125 (when using the anti-panic function (FAP))   SKG***
Technical installation situation	Inside and outside doors with maximum security requirements and subject to severe weather conditions   Suitable for installation in fire doors.
Compatible identification technologies	MIFARE DESFire EV1 + EV2
Battery	2 CR2 lithium batteries   Up to 70,000 cycles
Signals	Visual + acoustic
Conditions of use	Ambient temperature range: -20 °C to +55 °C (depending on the battery)   Humidity < 90 %, non-condensing   for 100,000 cycles as per EN 15684   35 mm minimum backset   IP65 protection
Event protocol	Last 1,000 events
Interfaces	Connection to Xesar tablet   BLE
Included components	Xesar cylinder   Cylinder fastening screw   2 CR2 lithium batteries   Assembly manual   Important information
Product code	E.X.PZ.HZ-S.[Outside cylinder length A/inside cylinder length l].[Finish].[Option]
Example	E.X.PZ.HZ-S.31/K31.NI

## Dimensional drawing



