

# EPS Cam lock | Coin operated lock cylinder



## Product description

The EPS cam lock DPM25 locks coin operated locks with flattened plug end on the side. It fits a hole pattern larger than 25 mm, is flattened on the side and is secured in the lock by a flat nut. Application examples are coin operated locks.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	28 <sup>1</sup>   34
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	DPM[...] – Coin operated lock Depomat®   LI – Left   RE – Right
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   up to 20 additional side codes with integrated manipulation control
Technical installation situation	In combination with a Depomat coin operated lock
Included components	Coin operated lock cylinder
Product code	M.[System].HB.DPM25.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin coin operated lock cylinder, diameter 25 mm, length 28 mm, nickel finish, right version: M.EPS5.HB.DPM25.28.NI.RE

<sup>1</sup> EPS5 und EPS5M only

## Dimensional drawing

