

# EPS Cam lock | Cam lock 19 mm SY-MO



## Product description

The EPS cam lock MB19-S locks boxes and cabinets with a cam on the rear. It is suitable for a hole pattern larger than 19 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are key boxes and mailboxes, display cases and technical distribution cabinets.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	23   28   33
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	0SN – Without cam   ST[...] – Locking direction A-H
Lever options	H[...]A] – Cam for metal boxes and display cases   HB[...]A] – Cam for mail boxes
Optional usage feature	B[...] – 2 key extracting positions   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   up to 20 additional side codes with integrated manipulation control
Technical installation situation	Hole pattern larger than 19 mm flattened on the side   rear mounted with a flat nut   locking cam according to dimensional drawing   for use in key cabinets, mailboxes as well as other metal sheet cabinets
Included components	Cylinder lock assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.[System].HB.MB19-S.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin cam lock, diameter 19 mm, length 23 mm, nickel finish, 2 key extracting positions at the bottom and left: M.EPS5.HB.MB19-S.23.NI.B01

## Dimensional drawing



