

## 4KS Cam lock | Cam lock 22 mm



### Product description

The 4KS cam lock MB22 locks boxes and cabinets with a cam at the rear. It is suitable for a hole pattern larger than 22 mm, is flattened on the side and is secured on the rear by a flat nut. Application examples are key boxes and mailboxes, display cases and technical distribution cabinets.

### Technical information

Cylinder length on the outside A in mm	27
Finish	NI – Nickel   MP – Polished brass   NP – Polished Nickel   MS – Brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	GTA[...] – Glass door plate wide   GTB[...] – Glass door plate high   SR22 – Dust and weather protection cover   ST[...] – Locking direction A-H
Lever options	H[...] [A] – Cam for metal boxes and display cases   HB[...] [A] – Cam for mail boxes
Optional usage feature	B01 – 2 key extracting positions 0°, 90°   B03 – 2 key extracting positions 0°, -90°   TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions)   12 springless, linear-controlled locking elements   Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Hole pattern larger than 22 mm flattened on the side   rear mounted with a flat nut   locking cam according to dimensional drawing   for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.4KS.HB.MB22.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS cam lock 22 mm diameter, nickel plated finish, length 27 mm, 2 key extracting positions at the bottom and left: M.4KS.HB.MB22.27.NI.B01

### Dimensional drawing

