

4KS Outside and inside cylinder | Inside cylinder 37 mm



Product description

The 4KS inside cylinder IZ37.SEC is suitable for use on the inside of the door. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with throughhole screws. Potential applications are Scandinavian mortise locks.

Technical information

Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Cylinder length on the outside A in mm	31
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Suitable for Scandinavian locks in combination with AZ37.SEC for 4-fold screw connections on the rear
Included components	Cylinder lock with cylinder cover and cover plate screws
Product code	M.4KS.AI.IZ37.SEC.[Finish]
Example	4KS Inside cylinder, 40 mm diameter, nickel plated finish: M.4KS.AI.IZ37.SEC.NI

Dimensional drawing

