

ICS rim cylinder | AZ37.SEC



Product description

The ICS outside cylinder AZ37.SEC is suitable for use on the outside of doors. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with rear throughhole screws. Potential applications are Scandinavian mortise locks.

Technical information

Finish	NI – Nickel MS – Brass NP – Polished Nickel MP – Polished brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional usage feature	TAF-A – Temporary Access Function outside VAR – VARIO
Accessories	Spray FinLube
Security features	Locking authorisation request on 5 tracks 13 spring-loaded locking elements Durable length profile Specially shaped locking elements as scanning protection, bump key protection and picking protection Hardened HSS steel pins in the cylinder plug as drilling protection Steel balls in the body as drilling protection 4-fold screwed
Standards and guidelines	EN 1303:2015 160B0C6D SS 3522 Category 3
Technical installation situation	Suitable for Scandinavian locks with high security requirements in combination with the IZ37-S.SEC for 4-fold screw fastening on the rear side
Included components	Cylinder lock with tail bar
Product code	M.ICS.AI.AZ37.SEC.[Finish].[Option]
Example	ICS outside cylinder, 37 mm diameter, nickel finish, with TAF: M.ICS.AI.AZ37.SEC.NI.TAF-A

Dimensional drawing

