

FPS Padlock | Padlock with insert, clearance width 24 mm



Product description

The FPS padlock HM24 with inserted cylinder insert has a shackle with a clearance width of 24 mm and is made of hardened steel. It is suitable for securing doors or objects that are equipped with hasps or eyelets. Potential applications are roller shutters, barrier systems, chain fastenings and barrier fences.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Niro/steel shackle variant, clear height in mm	S15 S30 N30 N40 N50 N60 N70 N80 N90 N100 N120 N150 N180 N200
Finish	NI – Nickel
Optional security features	BS – Shackle protection
Optional technical installation feature	SW-A – Dust and weather protection outside
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For use on doors with hasp and eyelet or for securing containers or chains.
Included components	Padlock
Product code	M.[System].HA.H30.[S/N clear height in mm].[Finish].[Option]
Example	FPS padlock 5-pin HM24, with stainless steel shackle, clearance height of 50 mm, nickel finish and rain drain hole: M.FPS5.HA.HM24.N50.NI.SW-A



Dimensional drawing

