

4KS Cam lock | Cam lock 22 mm for Kirner®



Product description

The 4KS cam lock MB22K locks boxes and cabinets with a rear 8 mm lock bar. It fits a hole pattern larger than 22 mm, is flattened on the side and is fastened at the rear by a flat nut. Application expamples are lockers and metal cabinets.

Technical information

Cylinder length on the outside A in mm	27 32 37
Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional technical installation feature	SR22 – Dust and weather protection cover ST[...] – Locking direction A-H
Optional usage feature	B01 – 2 key extracting positions 0°, 90° B03 – 2 key extracting positions 0°, -90° TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	Hole pattern larger than 22 mm flattened on the side rear mounted with a flat nut for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock with fastening nuts for cylinder and cam; also without cam
Product code	M.4KS.HB.MB22K.[Outside cylinder length A in mm].[Finish].[Option]
Example	4KS cam lock 22 mm diameter, nickel plated finish, length 27 mm, 2 key extracting positions at the bottom and left: M.4KS.HB.MB22K.27.NI.B01

Dimensional drawing

