

4KS Outside and inside cylinder | Rim cylinder 28 mm




Product description

The 4KS rim cylinder AZ28.AZG is suitable for use on the outside of the door. Surface mounted lock equipped with a vertical tail bar, fits a hole pattern larger than 28 mm and is rear mounted with throughhole screws. Application examples are rim locks and surface mounted locks.

Technical information

Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional technical installation feature	SPV – Twisted tail bar
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm TS76 – Door thickness 67 up to 76 mm TS86 – Door thickness 77 up to 86 mm
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in rim locks from other manufacturers up to door leaf thickness 56 mm
Included components	Cylinder with 2 M5x40 fixing screws
Product code	M.4KS.AI.AZ28.AZG.[Finish].[Option]
Example	4KS rim cylinder AZG, nickel plated finish with escutcheon: M.4KS.AI.AZ28.AZG.NI.R0U



Dimensional drawing

