

EPS Profile cylinder | Portal double cylinder



Product description

The EPS Portal double cylinder in compact design is suitable for portal doors. It locks with an integrated bolt directly into the prepared socket without a rim lock. The cylinder can be locked on both sides using an authorised key. Potential applications are display cabinets and shop windows.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	31 36
Cylinder length on the inside I in mm	31 36
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	BL-[...] – blind cylinder NS-[...] – Increased wear resistance SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements Features in cylinder as protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Technical installation situation	For use in portal doors without rim lock
Included components	Cylinder lock without screws
Product code	M.[System].PZ.PDZ.[Cylinder length on the outside A in mm/Cylinder length on the inside I in mm].[Finish].[Option]
Example	EPS 5-pin portal double cylinder, outside 31 mm, inside 36 mm, nickel finish, with VARIO option: M.EPS5.PZ.PDZ.31/36.NI.VAR

Dimensional drawing

