

FPS Profile cylinder | Double cylinder UK oval profile



Product description

The FPS UK double cylinder in compact design is suitable for use in outside and inside doors with a suitable UK oval profile lock. The cylinder features external key override. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	31 36 41 +5 ...
Cylinder length on the inside I in mm	31 36 41 +5 ...
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	PBP – Pretetermined Breaking Point
Optional technical installation feature	FL1 – Free wheel function SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For mortise locks suitable for UK oval profile Cam width 9.5 mm
Included components	Cylinder lock with mounting screw M5
Product code	M.[System].PZ.0DZ.[Outside cylinder length A in mm/Inside cylinder length I in mm]. [Surface].[Option]
Example	FPS Oval profile double cylinder 5-pin, outside 31 mm, inside 36 mm, nickel finish, optional blind outside: M.FPS5.PZ.0DZ.31/36.NI.BSZ

Dimensional drawing

