

FPS Insert cylinder | Profile cylinder insert



Product description

The FPS insert cylinder PZE.EK is suitable for use in conventional CISA® electric locks. It is equipped with a cam bar mounted on the rear side and holes in the plug. Suitable for a hole pattern with a diameter of 17 mm and a 6 mm wide bar recess in the electric lock. Fastening takes place in the lock case.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Cylinder length on the outside A in mm	FPS5: 22 FPS6: 27
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	Insert cylinder for the inner side of the "Elektrika" garden door strike.
Included components	Insert cylinder without fixing material
Product code	M.[System].EZ.PZE.EK.[Surface].[Option]
Example	FPS 5-pin insert cylinder for the inner side of the garden door strike "Elektrika", nickel finish, with re-coding function: M.FPS5.EZ.PZE.EK.NI.VAR



Dimensional drawing

