

FPS Cam lock | Coin operated lock cylinder



Product description

The FPS cam lock DPM25 locks coin operated locks with a flattened plug end on the side. It fits a hole pattern larger than 25 mm, is flattened on the side and is secured in the lock by a flat nut. Application examples are coin operated locks.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	28 ¹ 34
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	LI – Left RE – Right
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	In combination with a Depomat coin operated lock
Included components	Coin operated lock cylinder
Product code	M.[System].HB.DPM25.[Outside cylinder length A in mm].[Option]
Example	FPS 5-pin coin operated lock cylinder, diameter 25 mm, length 28 mm, nickel finish, right version: M.FPS5.HB.DPM25.28.NI.RE

¹ FPS5 only

Dimensional drawing

