

# ICS switching cylinder | AZ22



### Product description

The ICS switching cylinder AZ22 is suitable for use in various key switches. The cylinder does not have a cam bar on the rear, it fits a hole pattern larger than 22 mm with a 25 mm collar and is fastened in the switch by two screws on the back. Examples of applications are lift systems, escalators and control units.

### Technical information

Cylinder length on the outside A in mm	27
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	B[...] – 2 key extracting positions   D04 – 4 key extracting positions 0°, 90°, 180°, 270°
Accessories	Spray FinLube
Security features	Locking authorisation request on up to 5 tracks with spring-loaded locking elements   Durable length profile   Specially shaped locking pins as scanning protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	For use in switches with hole pattern larger than 22 mm with rear mounting
Included components	Switching cylinder
Product code	M.ICS.SZ.AZ22.27.[Finish].[Option]
Example	ICS switching cylinder AZ22, nickel finish, key removal top and bottom: M.ICS.SZ.AZ22.27.NI.B02



### Dimensional drawing

