

ICS push cylinder | DRZ25



Product description

The ICS push cylinder DRZ25 is suitable for use in metal and wooden sliding doors. The door is locked applying pressure on the rear of the cylinder. This requires a hole pattern larger than 25 mm and is rear mounted using a fixing plate. Examples of applications are office furniture with sliding doors.

Technical information

Cylinder length on the outside A in mm	29
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	KV05 – Plug end elongation 5 mm
Accessories	Spray FinLube
Security features	Locking authorisation request on up to 5 tracks with spring-loaded locking elements Durable length profile Specially shaped locking pins as scanning protection and picking protection Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	For installation in furniture sliding doors
Included components	Push cylinder
Product code	M.ICS.MZ.DRZ25.29.[Finish].[Option]
Example	ICS push cylinder, 25 mm, nickel finish, plug end extended: M.ICS.MZ.DRZ25.29.NI.KV05

Dimensional drawing

