

EPS Cam lock | Cam lock 30 mm



Product description

The EPS cam lock MB30 locks boxes and cabinets with a cam on the rear. It fits a hole pattern larger than 30 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are key boxes and mailboxes, display cases and technical distribution cabinets.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	26 ¹ 31 36
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	0SN – Without cam ST[...] – Locking direction A-H
Lever options	H[...]A – Cam for metal boxes and display cases HB[...]A – Cam for mail boxes
Optional usage feature	B[...] – 2 key extracting positions TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements up to 20 additional side codes with integrated manipulation control
Technical installation situation	Hole pattern larger than 30 mm flattened at the side rear mounted with a flat nut locking cam according to dimensional drawing for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.[System].HB.MB30.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin cam lock, diameter 30 mm, length 26 mm, nickel finish, without cam: M.EPS5.HB.MB30.26.NI.0SN

¹ EPS5 und EPS5M only

Dimensional drawing



