

Akura 44 | Double cylinder Euro profile modular



Technical information

Cylinder lengths	27/27, 27/30, 27/35, 30/27, 30/30, ... mm Starting at 30 mm in 5 mm steps
Finish	NI – Nickel MS – Brass CP – Polished chrome CPV – Chrome fully polished CR – Chrome ML – Brass lacquered MP – Polished brass MPV – Brass fully polished NP – Polished Nickel NPV – Nickel fully polished PB – Patinated brown PS – Patinated black
Optional security features	AS-A – Anti-Snap outer side BSZ – External key override FZG – Free wheel function for gear locks MAG – Magnetic copying protection VDS – VdS certified
Optional technical installation feature	BIF – Double cam Biffar® BL-[...] – Blind cylinder FL1 – Free wheel function LW[...] – Free travel NS[...] – Increased wear resistance SEW – Sea water protection SW[...] – Dust and weather cover Z[...] – Cogwheel
Optional usage feature	BIF – Double cam Biffar® BL-[...] – Blind cylinder BSZ – External key override FL1 – Free wheel function FZG – Free wheel function for gear locks LW[...] – Free travel NS[...] – Increased wear resistance PAR – Partner cylinder SEW – Sea water protection TXT – Customer-specific text VAR – VARIO Z[...] – Cogwheel
Function	Can be locked on both sides with key Reversible key
Usage	connecting doors entrance doors apartment entrance metal frame door security doors
Security	Pin rows: 3 Active pins: 6 Passive pins: 10 Drilling protection Pulling protection Picking protection Security card
Standards	EN 1303:2015 160B0C6B ÖNORM B5351: WZ6-B ČSN EN 1627, Security class 4 BSI* Fire resistance 90 minutes
Assembly	Mortise lock according to DIN, ÖNORM Surface mounted locks for Euro profile Modular design Cam width 9,3 mm
included components	Cylinder lock Fixing screw M5
Product code	M.A44.PZ.DZ-M.[Cylinder length].[Finish].[Options]

Dimensional drawing

