


# EPS Switch and switching cylinder | Lift cylinder 28 mm



## Product description

The EPS lift cylinder MR28 is suitable for use in various lift control systems. It has no rear side cam bar, it has a hole pattern larger than 28 mm, and is fastened by two screws at the rear. Application examples are lift systems and escalators.

## Technical information

System	EPS5 – Extended Profile System 5 pin   EPS5M – Extended Profile System Trademark protection 5 pin   EPS6 – Extended Profile System 6 pin   EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	26 <sup>1</sup>   31
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements   up to 20 additional side codes with integrated manipulation control
Technical installation situation	For use in lifts or lift controls with a hole pattern larger than 28 mm
Included components	Lift cylinder without cam bar
Product code	M.[System].SZ.MR28A.[Cylinder length on the outside A in mm].[Finish].[Option]
Example	EPS 5-pin lift cylinder, length 26 mm, nickel finish: M.EPS5.SZ.MR28A.26.NI

## Dimensional drawing

