

# ICS rim cylinder | AZ28.AZI



## Product description

The ICS AZ28.AZI rim cylinder is suitable for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 28 mm and is secured on the rear side with throughhole screws. Application examples are rim locks and surface mounted locks.

## Technical information

Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   MP – Polished brass   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   PS – Patinated black   PB – Patinated brown
Optional security features	SKG2-A – SKG ** certified outside   SKG3-A – SKG *** certified outside
Optional technical installation feature	APA – Fixing plate ABUS®   GWB6 – 1 thread M6   R0A – Escutcheon ABUS®   R0SKG – Escutcheon SKG
Door leaf thickness options	TS66 – Door thickness 57 up to 66 mm   TS76 – Door thickness 67 up to 76 mm   TS86 – Door thickness 77 up to 86 mm
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Locking authorisation request on 5 tracks   13 spring-loaded locking elements   Durable length profile   Specially shaped locking elements as scanning protection, bump key protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection   Steel balls in the body as drilling protection
Technical installation situation	In combination with ABUS® rim locks up to door leaf thickness 56 mm
Included components	Cylinder lock with 2 M5×40 fixing screws (with GWB6 M6×40 option)
Product code	M.ICS.AI.AZ28.AZI.[Finish].[Option]
Example	ICS rim cylinder for ABUS rim locks, nickel finish with M6 holes: M.ICS.AI.AZ28.AZI.NI.GWB6

## Dimensional drawing



