

4KS Outside and inside cylinder | Rim cylinder 29 mm



Product description

The 4KS rim cylinder AZ29.MB is suited for use on the outside of the door. It is equipped with a horizontal tail bar for surface mounted locks, fits a hole pattern larger than 29 mm and is secured on the rear side with throughhole screws. Potential applications are rim locks and surface mounted locks.

Technical information

Finish	NI – Nickel MP – Polished brass NP – Polished Nickel MS – Brass ML – Brass lacquered CR – Chrome CP – Polished chrome PS – Patinated black PB – Patinated brown
Optional technical installation feature	HU38 – Spacer sleeve length 38,5 mm
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Technical installation situation	For use in various rim locks with horizontal tail bar mount up to door leaf thickness 76 mm
Included components	Rim cylinder with 2 M5×60 fixing screws
Product code	M.4KS.AI.AZ29.MB.[Finish].[Option]
Example	4KS rim cylinder, diameter 29 mm (AZG sleeve) with centred drilling, nickel plated finish: M.4KS.AI.AZ29.MB.NI.HU38

Dimensional drawing

