

# FPS Cam lock | Cam lock 22 mm



## Product description

The FPS cam lock MB22 locks boxes and display cabinets with a locking cam at the rear. It is suitable for a hole pattern larger than 22 mm, is flattened on the side and fastened at the rear by a flat nut. Application examples are key boxes and letter boxes, display cabinets and technical distribution cabinets.

## Technical information

System	FPS5 – Functional Profile System 5 pin   FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	27 <sup>1</sup>   32   37
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Optional technical installation feature	0SN – Without cam   GKG – Door knob 38 mm for glass doors   GTA[...] – Glass door plate wide   GTB[...] – Glass door plate high   SR22 – Dust and weather protection cover   ST[...] – Locking direction A-H
Lever options	H[...]A – Cam for metal boxes and display cases   HB[...]A – Cam for mail boxes
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	Hole pattern larger than 22 mm flattened on the side   rear mounted with a flat nut   locking cam according to dimensional drawing   for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock assembled with fastening nut and standard cam H7233 or optional cam
Product code	M.[System].HB.MB22..[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS 5-pin cam lock, diameter 22 mm, length 27 mm, nickel finish, 2 key extracting positions at the bottom and left: M.FPS5.HB.MB22.27.NI.B01

<sup>1</sup> FPS5 only

## Dimensional drawing

