

# ICS lift cylinder | MR28A




### Product description

The ICS lift cylinder MR28A is suitable for use in various lift control systems. It has no rear side cam bar, it has a hole pattern larger than 28 mm, and is fastened by two screws at the rear. Application examples are lift systems and escalators.

### Technical information

Cylinder length on the outside A in mm	26   31
Finish	NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown
Accessories	Spray FinLube
Security features	Locking authorisation request on up to 5 tracks with spring-loaded locking elements   Durable length profile   Specially shaped locking pins as scanning protection and picking protection   Hardened HSS steel pins in the cylinder plug as drilling protection
Technical installation situation	For use in lifts or lift controls with a hole pattern larger than 28 mm
Included components	Lift cylinder without cam bar
Product code	M.ICS.SZ.MR28A.[Outside cylinder length A in mm].[Finish].[Option]
Example	ICS lift cylinder, 28 mm, nickel finish, length 26 mm: M.ICS.SZ.MR28A.26.NI



### Dimensional drawing

