

FPS Cam lock | Cam lock 22 mm for Kirner®



Product description

The FPS cam lock MB22K locks the lock bar of boxes and display cabinets with a rear 8 mm square spindle. It fits a hole pattern larger than 22 mm, is flattened on the side and is fastened at the rear by a flat nut. Application examples are lockers and metal cabinets.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	27 ¹ 32 37
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	GKGT – Door knob 38 mm for glass doors SR22 – Dust and weather protection cover ST[...] – Locking direction A-H
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements
Technical installation situation	Hole pattern larger than 22 mm flattened on the side rear mounted with a flat nut for use in key boxes, mailboxes and other sheet metal cabinets
Included components	Cylinder lock with fixing nuts for cylinder and cam; also without cam
Product code	M.[System].HB.MB22K.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS 5-pin cam lock, diameter 22 mm, length 27 mm, nickel finish, 2 key extracting positions at the bottom and left: M.FPS5.HB.MB22K.27.NI.B01

¹ FPS5 only

Dimensional drawing

