

EPS Profile cylinder | Double cylinder UK oval profile



Product description

The EPS UK double cylinder in compact design is suitable for use in external and internal doors in combination with an UK oval profile. The cylinder features external key override. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

System	EPS5 – Extended Profile System 5 pin EPS5M – Extended Profile System Trademark protection 5 pin EPS6 – Extended Profile System 6 pin EPS6M – Extended Profile System Trademark protection 6 pin
Cylinder length on the outside A in mm	31 36 41 +5 ...
Cylinder length on the inside I in mm	31 36 41 +5 ...
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional security features	PBP – Pretetermined Breaking Point
Optional technical installation feature	BL-[...] – blind cylinder NS-[...] – Increased wear resistance SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system with 5 or 6 active, spring-loaded locking elements Features in cylinder as protection against covert opening methods Up to 20 additional side codes with integrated tampering control Hardened steel elements as drilling protection
Technical installation situation	For mortise locks suitable for UK oval profile Cam width 9.5 mm
Included components	Cylinder lock with mounting screw M5
Product code	M.[System].PZ.0DZ.[Cylinder length on the outside A in mm/Cylinder length on the inside I in mm].[Finish].[Option]
Example	EPS Oval profile double cylinder 5-pin, outside 31 mm, inside 36 mm, nickel finish, optional blind outside: M.EPS5.PZ.0DZ.31/36.NI.BL-A

Dimensional drawing



