

# FPS Outside and inside cylinder | Rim cylinder 28 mm



## Product description

The FPS AZ28.AZI rim cylinder is suited to use on the outside of the door. surface mounted lock equipped with a vertical tail bar, fits a hole pattern larger than 28 mm and is rear mounted with throughhole screws. Application examples are rim locks and surface mounted .

## Technical information

|   |  |
|---|--|
| System                                  | FPS5 – Functional Profile System 5 pin   FPS6 – Functional Profile System 6 pin  |
| Finish                                  | NI – Nickel   MS – Brass   NP – Polished Nickel   NPV – Nickel fully polished   MP – Polished brass   MPV – Brass fully polished   ML – Brass lacquered   CR – Chrome   CP – Polished chrome   CPV – Chrome fully polished   PS – Patinated black   PB – Patinated brown |
| Optional technical installation feature | SPV – Twisted tail bar   |
| Door leaf thickness options             | TS66 – Door thickness 57 up to 66 mm   TS76 – Door thickness 67 up to 76 mm   TS86 – Door thickness 77 up to 86 mm   |
| Optional usage feature                  | VAR – VARIO  |
| Accessories                             | Spray FinLube  |
| Cylinder length on the outside A in mm  | FPS5: 22   FPS6: 27  |
| Security features                       | Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements   Features in the cylinder protect against covert opening methods   hardened steel elements for drilling protection   |
| Technical installation situation        | For use in various rim locks from other manufacturers up to door leaf thickness 56 mm  |
| Included components                     | Cylinder lock with 2 M5x40 fixing screws   |
| Product code                            | M.[System].AI.AZ28.AZG.[Surface].[Option]  |
| Example                                 | FPS rim cylinder AZG 5-pin, nickel finish with twisted tail bar: M.FPS5.AI.AZ28.AZG.NI.SPV   |

## Dimensional drawing



