

FPS Outside and inside cylinder | Outside cylinder 37 mm



Product description

The FPS outside cylinder AZ37.SEC is suitable for use on the outside of doors. It is equipped with horizontal cam bar for mortise locks, fits a hole pattern larger than 40 mm and is fastened with rear throughhole screws. As an example, they can be used in Scandinavian mortise locks.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional usage feature	VAR – VARIO
Accessories	Spray FinLube
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Standards and guidelines	SS 3522 Klasse 3
Technical installation situation	Suitable for Scandinavian locks with high security requirements in combination with the IZ37.SEC for 4-fold screw fastening on the rear side
Included components	Cylinder lock with tail bar
Product code	M.[System].AI.AZ37.SEC.[Finish].[Option]
Example	FPS outside cylinder 5-pin, 37 mm diameter, nickel finish, with TAF: M.FPS5.AI.AZ37.SEC.NI.TAF-A

Dimensional drawing

