

4KS Profile cylinder | Thumbturn cylinder Swiss round profile SY-MO



Product description

The 4KS round profile thumbturn cylinder in modular design (SY-MO) is suitable for use in external and internal doors. The cylinder is locked on the outside with an authorised key and on the inside with a thumbturn. Potential applications are doors to residential properties or offices, connecting doors, metal frame doors and security doors.

Technical information

Cylinder length on the outside A in mm	31 36 41 46 +5 ...
Cylinder length on the inside I in mm	K31 K36 K41 K46 +5 ...
Finish	NI – Nickel MP – Polished brass NPV – Nickel fully polished MS – Brass NP – Polished Nickel MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Thumbturn shape	OKA – Oval thumbturn aluminium asym. AK – Allround thumbturn ATA – Adaptable Thumbturn Axis CK – D-line® thumbturn FK – Flat thumbturn GK – Recessed grip thumbturn KK – Cone thumbturn MK – Metal knurl thumbturn NOK – Without thumbturn RK – Round thumbturn
Thumbturn finish	K-CP – Polished Chrome K-CR – Chrome K-EF2 – Aluminium F2 K-EF3 – Aluminium F3 K-MP – Polished brass K-MS – Brass K-NI – Nickel K-NP – Polished nickel K-PB – Patinated brown K-PS – Patinated black
Optional security features	S0S – SOS function
Optional technical installation feature	BL-A – Blind outside KS-A – Contact pin outside SEW – Sea water protection SW-A – Dust and weather protection outside Z10 – Cogwheel cam Z10 Z18 – Cogwheel cam Z18
Optional usage feature	TXT – Customer-specific text
Accessories	Spray FinLube Cylinder fixing screw
Security features	Locking authorisation request in at least 18 scanning positions (authorisation positions) 12 springless, linear-controlled locking elements Security elements made of tungsten carbide or hardened steel to prevent drilling and pulling
Standards and guidelines	90 minutes
Technical installation situation	For mortise locks and surface mounted locks suitable for the installation of round profile cylinder locks Cam width 8.5 mm
Included components	Cylinder with thumbturn and fixing screw M5
Product code	M.4KS.PZ.RKZ-S.[Outside cylinder length A in mm/Inside cylinder length I in mm]. [Finish].[Thumbturn shape].[Thumbturn finish].[Option]
Example	4KS round profile thumbturn cylinder, outside 31 mm, inside 36 mm, nickel plated finish, with KK thumbturn and optional priority function: M.4KS.PZ.RKZ-S.31/K36.NI.KK.K-NI.SOS

Dimensional drawing



